
HYDFLEX [::

ELECTRIC CRIMPING MACHINE

NK-60

The strongest crimper in the NK series. This machine is meant for professional hose assembly production. The crimping force of 320 tons and a max dieless head opening of 180 mm allow it to crimp 2SN hoses of up to 4" ID (DN 100 mm)





TECHNICAL SPECIFICATIONS

MODEL	NK-60
DIMENSIONS	500 mm x 700 mm x 820 mm
WEIGHT	340 kg
MAX CRIMPING FORCE	350 ton
MAX OPENING WITH DIES	Ø + 54 mm
MAX OPENING WITHOUT DIES	180 mm
MASTER DIE SIZE D/L	120 mm
MAX INSIDE DIAMETERS	2 WIRES (2SN) 4" (DN 100 mm)
OF CRIMPED HOSES	4 WIRES (4SP) 2" (DN 50 mm)
	6 WIRES 2" (DN 50 mm)
	Maximal size of elbow BSP 3"
	Maximal dimension of crimping 145 mm
	Minimal dimension of crimping 4 mm
MOTOR POWER	4 kW – 400V 3-PH 50hz (KP-60.V-1)
	4 kW – 400V 3-PH 50Hz (KP-60.E-1)
DIES DIMENSIONS	Die Ø mm 04 06 08 10 12 15 18 21 24 27 30 33 39 45 48 51 54 57 62 6
	Length mm 56 70 100
	Die Ø mm 73 80 86 90 96 106 116 122 130 136
	Length mm 125
ACCESSORIES	PDP.1 - Single die change tool

ACCESSORIES

22

This model is also available with a separate head and motor, which reduces its weight and allows for easier mounting in mobile workshops

PDR-1 – Single die change tool

ST-12-PDR – Workshop desk, complete with 12 die set storage panel

WP-12-PDR – Die set panel to store 12 die sets

QCG-NLS – Quick change tool for entire die sets





NK-60

HYDFLEX []::













23